



## DESCRIPTION

**SPECIALE** is a highly adherent antifouling and elastic and is effective in fresh water, sea water and brackish water. It is used on the propellers of boats of all kinds. Adheres tenaciously on all surfaces. Suitable for all aluminium parts immersed.

## INFORMATION

Fuori polvere Dust Free <b>20 min</b>	Immersione Splashing <b>8 h</b>	Resa Spreading <b>12m<sup>2</sup>/lt</b>	Ugelli Tips <b>0,017- 0,021</b>	Diluizione Thinning <b>Diluyente 01</b>			
---------------------------------------------	---------------------------------------	------------------------------------------------	-------------------------------------------	---------------------------------------------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

## TECHNICAL DATA

<b>TYPE</b>	One component
<b>COLOR</b>	Black – White – Grey
<b>ASPECT</b>	Mat
<b>DENSITY</b>	1.40±0.05 g/cm <sup>3</sup>
<b>SOLID CONTENT</b>	65% Vol
<b>MIX RATIO</b>	NA (one component)
<b>SANDING</b>	Yes
<b>COVERING LONG-TERM</b>	Yes
<b>SPREADING</b>	~12 mq/lt at 50 mic.
<b>COMPATIBILITY ON ALUMINIUM</b>	Yes
<b>THINNER</b>	Diluyente 01
<b>SHELF LIFE</b>	2 Years

## DRYING INFORMATION (T20°C)

<b>Splashing</b>	<b>8 h</b>
------------------	------------

## SPECIALE

### Extra Hard Matrix for Propellers

**Minimum Dry film Thickness per coat** 100 micron

**Application Methods**



Y



Y



Y

**Thinner**

-

-

10%

#### GENERAL INFORMATION

Do not expose to heat sources and under the sun. For best preservation of **SPECIALE** be sure that when stocked the cans are well closed and the temperature is between 5°C/40°F and 35°C/95°F.

#### TRASPORTATION

**SPECIALE** must be kept in closed cans and drums during transportation.

#### DESCRIPTIONS FOR USE

Carefully mix the product before use. The technical data are determined at 20° C unless otherwise designation and refer to the product ready for use and undiluted.

#### GENERAL

Always read the technical and safety advices reported on labels. Obtain further safety and technical advice from our technical support. **DISPOSAL:** Do not dispose the empty cans or residues of paint in the environment; use adequate disposal containers. It is preferred to dispose the paint residues when are in solid state. Residues of **SPECIALE** cannot be disposed as normal waste but only as special dangerous waste. The disposal must be done following the local regulations about dangerous waste. Consult local authorities for advice.

#### IMPORTANT NOTES

The information contained in this TDS must not considered exhaustive. Any use without written and certified advice from SAFE NANOTECHNOLOGIES technical support does it at his own risk and danger. In this case SAFE NANOTECHNOLOGIES does not take any responsibility for the coating performance and any damage deriving from such uncorrect use of the product apart when it is proven that the damages are due to our negligence. The information contained in this sheet could be subject to modification due to our improved experience and to our polithics of product developmenmt.

Rev. N. 05 October 2013